


RhinoRoof® U20

Synthetic Roofing Underlayment

RhinoRoof U20 Technical Data



U20 ROLL & PALLET SPECIFICATIONS	
LENGTH PER ROLL:	286' / 87 m
WIDTH PER ROLL:	42" / 1.1 m
WEIGHT PER ROLL:	23.5 lbs / 10.6 kg
ROLL SIZE:	10 sq / 93 m ²
ROLLS PER PALLET:	67
PALLET WEIGHT:	1,626 lbs / 738 kg

TEST & ASTM STANDARD	RHINOROOF U20 TYPICAL VALUE	#15 FELT TYPICAL VALUE
Permeability E96	.05 perms	5 perms
Water Transmission D4869	Pass	Pass
Tear Strength D4533	MD 26 lbs (12 kg) CD 24 lbs (11 kg)	MD 2.2 lbs (1 kg) CD 0.9 lbs (0.4 kg)
Tensile Strength D751	MD 88 lbs (40 kg) CD 70 lbs (32 kg)	MD 54 lbs (24.5 kg) CD 29 lbs (13.2 kg)
Burst Strength D751	158 psi (1089 kPa)	35 psi (242 kPa)
Elongation D751	MD 20% CD 20%	MD 3% CD 4%
Weight per Square D5261	2.25 lbs (1.02 kg)	11.2 lbs (5 kg)
Nominal Thickness D1777	7 mils (0.18 mm)	21 mils (0.525 mm)
Temperature Range	-40 °F to 240 °F (-40 °C to 115 °C)	14 °F to 212 °F (-10 °C to 100 °C)

RhinoRoof U20 Building Codes



- Meets ASTM D4869 & D226 Types I & II
- Florida Building Code Approved # FL15216
- Texas Department of Insurance
- Warnock Hersey
- CAN/CSA A123.3
- CCRR-1015



weaving a better word™



1-800-453-0349

