

Safety Data Sheet

Page 1 of 6

MSDS-No.: 250222 V000.0

Date of issue: 02.07.2015

LOCTITE EPOXY INSTANT MIX 5MIN (HARDENER)

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE EPOXY INSTANT MIX 5MIN (HARDENER)

Intended use: 2-Component epoxy adhesive

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137

Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

Hazard ClassHazard CategorySkin irritationCategory 2Serious eye irritationCategory 2A

Hazard pictogram:



Signal word: Warning

Hazard statement(s): H315 Causes skin irritation.
H319 Causes serious eye irritation.

Precautionary Statement(s):

Prevention: P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response: P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing.

MSDS-No.: 250222 V000.0

LOCTITE EPOXY INSTANT MIX 5MIN (HARDENER)

Risk phrases:

R36/38 Irritating to eyes and skin.

Safety phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of water.

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S46 If swallowed, seek medical advice immediately and show this container or label.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Signal word:

HAZARDOUS

Section 3. Composition / information on ingredients

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
1,3-bis[3-(dimethylamino)propyl]urea	52338-87-1	10- 30 %
non hazardous ingredients~		60- 100 %

Section 4. First aid measures

Ingestion: Do not induce vomiting.

Have victim rinse mouth thoroughly with water.

Seek medical advice.

Skin: Immediately flush skin with plenty of water (using soap, if available).

Seek medical attention from a specialist.

Eyes: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical attention from a specialist.

Inhalation: Move to fresh air.

Keep warm and in a quiet place.

If adverse health effects develop seek medical attention.

First Aid facilities: Eye wash and safety shower

Normal washroom facilities

Medical attention and special

treatment:

Treat symptomatically.

Section 5. Fire fighting measures

Suitable extinguishing media: Carbon dioxide, foam, powder

Fine water spray

MSDS-No.: 250222 V000.0

LOCTITE EPOXY INSTANT MIX 5MIN (HARDENER)

Improper extinguishing media: Water spray jet

Decomposition products in case of

fire::

Thermal decomposition can lead to release of irritating gases and vapors.

Carbon monoxide. Carbon dioxide. Oxides of nitrogen.

Special protective equipment for

fire-fighters:

Wear protective equipment.

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

Collect contaminated fire fighting water separately. It must not enter drains.

Section 6. Accidental release measures

Personal precautions: Danger of slipping on spilled product.

Ensure adequate ventilation. Avoid skin and eye contact.

Wear impervious gloves and chemical splash goggles.

Environmental precautions: Do not empty into drains / surface water / ground water.

Clean-up methods: Collect spilled material with an inert absorbent such as sand or vermiculite. Place in

properly labeled closed container.

Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Precautions for safe handling: Gloves and safety glasses should be worn

Avoid skin and eye contact.

Ensure that workrooms are adequately ventilated. Avoid breathing vapors or mists of this product.

Conditions for safe storage: Keep container tightly sealed.

Store in a cool, dry, well-ventilated area.

Protect from direct sunlight.

Temperatures between + 5 °C and + 35 °C

Section 8. Exposure controls / personal protection

National exposure standards:

None

MSDS-No.: 250222

V000.0 LOCTITE EPOXY I

LOCTITE EPOXY INSTANT MIX 5MIN (HARDENER)

Engineering controls: Use general ventilation and use local exhaust, where possible, in confined or enclosed

spaces.

Eye protection: For eye protection, use tightly fitted safety goggles and a face-shield

Skin protection: Use of protective coveralls and long sleeves is recommended.

Suitable protective gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance: Clear

Viscous, Liquid

 Odor:
 None

 pH:
 3 - 5

 Specific gravity:
 1.1000

Boiling point: > 149 °C (> 300.2 °F) **Flash point:** 257 °C (494.6 °F)

(no method)

Density: 1.00 - 1.10 g/cm3 **Solubility in water:** Dispersible (23 °C)

Section 10. Stability and reactivity

Stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Heat, flames, sparks and other sources of ignition.

Excessive heat.

Store away from incompatible materials.

Incompatible materials: Acids.

Strong oxidizing agents.

This product may react with metals, halogens.

Alkalis.

Hazardous decomposition

products:

Thermal decomposition can lead to release of irritating gases and vapors.

Carbon monoxide. Carbon dioxide. Oxides of nitrogen.

Hazardous polymerization: Will not occur.

Section 11. Toxicological information

MSDS-No.: 250222

V000.0

LOCTITE EPOXY INSTANT MIX 5MIN (HARDENER)

Health Effects:

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Skin: Causes skin irritation.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Eyes: Causes serious eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Inhalation: Inhalation of vapors or mist can cause severe irritation, tissue and scarring of the respiratory tract.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
1,3-bis[3-						
(dimethylamino)propyl]ur	LD50	> 5,000 mg/kg	oral			
ea						
52338-87-1						

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Section 13. Disposal considerations

Waste disposal of product: Dispose of as hazardous waste in compliance with local and national regulations.

Do not allow product to enter sewer or waterways.

Disposal for uncleaned package: Dispose of as hazardous waste in compliance with local and national regulations.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

UN no.: 3334

Proper shipping name: Aviation regulated liquid, n.o.s. (Mercaptan polymer)

Class or division: 9
Packing group: III
Packing instructions (passenger) 964
Packing instructions (cargo) 964

Section 15. Regulatory information

MSDS-No.: 250222 V000.0

LOCTITE EPOXY INSTANT MIX 5MIN (HARDENER)

Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

IMDG: International Maritime Dangerous Goods code

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

Reason for issue: First issue. involved chapters: 1 - 16

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material. The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet. This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.