



**MFM Building Products Corp.** manufactures a wide range of innovative waterproofing products for the building industry. Founded in 1961, MFM products are engineered for superior performance and ease of installation.

### DESCRIPTION

MFM Low VOC Spray Adhesive™ is designed and tested for use with all MFM self-adhering products. Use to enhance adhesive properties and extend the application temperature range. This high strength, fast tack, high shear adhesive is ideal for use with Peel & Seal®, SubSeal™, FlexClad™, WindowWrap® and other MFM Products. High temperature rated, fast tack and VOC compliant.

### APPLICATION

#### Follow Instructions Carefully

- Shake can thoroughly for 60 seconds before use
- Surface for application should be clean and dry
- Hold can perpendicular to substrate approx. 8"-12" (20-30 cm) from the surface
- Apply a light, even coating to the substrate at temperatures above 35°F (1.7°C)
- DO NOT spray directly onto self-adhering membrane
- Avoid excessive build-up or puddles on substrate
- Before applying self-adhering membrane, allow spray adhesive to cure for 2-3 minutes, depending on humidity and wind conditions, or until the surface no longer appears or feels wet – do not exceed more than 10 minutes
- Apply the self-adhering membrane onto the substrate and apply even pressure to the entire membrane with a hand roller
- Monitor adhesion as you go – stop installation if the membrane is not properly adhering

**MFM Low VOC Spray Adhesive must cure 2-3 minutes before membrane is applied.**

### PACKAGING

MFM Low VOC Spray Adhesive is available in a 14 oz. (397 grams) aerosol spray can. Packaged 12 cans per carton.

### WARNINGS

- Roof work is dangerous – work carefully
- Keep cans in a cool, well ventilated area at 70°F (21°C) for optimum performance – do not store above 122°F (50°C)
- Follow warnings and instructions on can
- **DO NOT** spray adhesive in eyes or near face
- **DO NOT** puncture or incinerate container
- **DO NOT** dispose of empty container in trash compactor
- Dispose empty containers in accordance with applicable local, county, state and federal regulations

**For exterior use only. Use with adequate ventilation. Keep out of reach of children. Read and understand all information on can label before use.**

### PRODUCT DATA

Application Temperature	<35°F (<1.7°C)
Bonding Time	5-10 minutes
Coverage per Can	50-60 ft <sup>2</sup> (4.6-5.6 m <sup>2</sup> )
VOC Content	25.15% by volume
VOC Compliant CARB/OTC	Yes
Recyclable Packaging	Yes
Ozone-Depleting Compounds	No
Packaging	14 oz. aerosol can (397 grams)
Shipping Quantity	12 cans per carton
Shipping Designation	Class 55
Weight per Can	1 lb. (0.45 kg)
Weight per Carton	14.5 lbs. (6.6 kg)
Shelf Life	1 Year+

### PRODUCT NUMBER | PRODUCT UPC CODE

90005      14 oz. Spray Can      7 25799 90001 9

**For the most current Installation Instructions, Warranties, Technical Specifications and Approvals, visit [www.mfmbp.com](http://www.mfmbp.com).**

**MFM Spray Adhesive cannot be shipped via Air Shipments.**



**Product does not contain any chemicals listed under California Proposition 65.**

