

PRETON R-720B

Appearance	Brown Liquid
Density (15°C , g/cm ³)	0.89
Viscosity (40°C , mm ² /s)	45.0
Flash point (°C)	>160°C
Pour point (°C)	Below-10°C
Packing type	18L can , 200L drum
Humidity Cabinet test (SPCC)	720 hours A class (no rusting)
Characteristics	<ul style="list-style-type: none">※ PRETON R-720B is a rust prevention oil.※ PRETON R-720B had a strong anticorrosion.※ It is suited to the anticorrosion of exporting parts, and the long-term preservation purposes indoors.

(The values above are representative)

 **PEI SUN(JINAN) CO.,LTD.** 

ADDRESS : South of Huitong Street and west of Shengwei Road, Xiaozhi Town, Pingyin County, Jinan City,
Shandong Province , 250402 , China

TEL : +86-531-8570-8090
<http://www.peisun.com>

FAX : +86-531-8570-8014
e-mail : jinan@peisun.com

MATERIAL SAFETY DATA SHEET

PEI SUN (JINAN) CO., LTD

South of Huitong Street and west of Shengwei Road, Xiaozhi Town, Pingyin County, Jinan City,
Shandong Province · 250402 · China

TELEPHONE: +86-531-8570-8090

Designed to meet the requirements 29CFR1910.1200
OSHA Hazard Communication Standard

Page 1

N/D=Not Determined
N/A=Not Applicable

SECTION I : IDENTIFICATION

IDENTITY	R-720B		
CHEMICAL FAMILY	Rust prevention oil	REVISION DATE: Apr.20, 2018	
EMERGENCY PHONE NUMBER	+86-531-8570-8090		

SECTION II : HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	OSHA PEL	ACGIH TLV	%

SECTION III : PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT (Degrees Fahrenheit min)	N/A	DENSITY (15°C,g/cm ³)	0.89
VAPOR PRESSURE (mm/Hg @ 70F)	N/A	PERCENT VOLATILE BY VOLUME	N/A
VAPOR DENSITY (Air = 1)	N/A	MELTING POINT (Degrees Fahrenheit max)	N/A
SOLUBILITY IN WATER	Negligible	PH	N/D
EVAPORATION RATE (n-butyl acetate)	N/A		

APPEARANCE AND ODOR: Brown Liquid – Mild Odor

SECTION IV : FIRE AND EXPLOSION HAZARD DATA

FLASH POINT
(°C) > 160

FLAMMABLE LIMITS	LEL	UEL	AUTO-IGNITION TEMPERATURE (°C min)	N/A
	N/A	N/A		

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, or form. Foam may cause frothing or spattering, and should be applied carefully.

SPECIAL FIRE FIGHTING PROCEDURES: Water self-contained breaching apparatus.
Keep fire exposed containers cool with water.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Hot vapors form explosive mixtures with air.

SECTION V : REACTIVITY DATA

STABILITY:	Unstable	
	Stable	×

CONDITIONS TO AVOID: Sparks and open flames

INCOMPATIBILITY: Strong acids and oxidants

HAZARDOUS DECOMPOSITION PRODUCTS: Fumes and smoke possibly including CO, CO₂ on combustion

HAZARDOUS POLYMERIZATION	May occur	
	Will not	×

CONDITION TO AVOID: None

SECTION VI: HEALTH HAZARD DATA

PRIMARY ROUTES OF EXPOSURE:	INHALATION	SKIN	INGESTION
	×	×	×

HEALTH HAZARDS:

SKIN CONTACT: Prolonged or repeated skin contact may remove natural oils, and cause irritation.

EYE CONTACT: Causes eye irritation upon contact.

INGESTION: This product has a low order of acute oral toxicity, but small amount aspirated into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury.

SIGNS AND SYMPTOMS OF EXPOSURE: Excessive oil mist inhalation may cause dizziness, nausea, and difficulty breathing.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: Sensitive skin.

EMERGENCY AND FIRST AID PROCEDURES:

SKIN CONTACT: In case of contact, wash skin with warm water and mild soap. Wash clothing before reuse.

EYE CONTACT: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

INGESTION: If swallowed, call a physician immediately. ONLY induce vomiting at the instruction of physician. Never give anything by mouth to an unconscious person.

SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IF MATERIAL RELEASED OR SPILLED: In case of spill, evacuate area and secure sources of ignition. Clean up spill immediately. Avoid contamination of sewers and waterways. Wear approved respiratory equipment during cleanup if area is not ventilated adequately. Soak up with sand, earth or other inert material.

WASTE DISPOSAL METHODS: Dispose of in accordance with local and federal regulations. Avoid contamination sewers and waterways.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Avoid contact with eyes, skin and clothing. Remove contaminated clothing, and launder before reuse. Wash thoroughly after handling. Keep container tightly closed and away from sparks or flames.

OTHER PRECAUTIONS: Since emptied containers retain product residue, follow label warnings even after container is emptied.

SECTION VIII: CONTROL MEASURES

RESPIRATORY PROTECTION: Not normally required.

VENTILATION: Provide general ventilation and local exhaust sufficient to prevent exceeding exposure limits.

PROTECTIVE GLOVES	Oil impervious to avoid prolonged/repeated contact.
--------------------------	-----------------------------------------------------

EYE PROTECTIVE	Safety glasses or goggles for splash protection.
-----------------------	--------------------------------------------------

OTHER PROTECTIVE EQUIPMENT	Use as required to avoid prolonged or repeated skin contact.
-----------------------------------	--------------------------------------------------------------

HYGENIC PRACTICES: Wash thoroughly before meals, breaks, and at the end of work period. Remove contaminated clothing and launder before reuse.

SECTION IX : ENVIRONMENTAL

Contains no ingredients subject to release reporting;
TOXIC SUBSTANCES CONTROL ACT;

WE BELIVE THE STATEMENTS, TECHNICAL INFORMATION AND
RECOMMENDATIONS CONTAIN HEREIN ARE RELIABLE, BUT THEY ARE
GIVEN WITHOUT WARRANTY OR GUARANTEE OF ANY KIND, EXPENSE,
DIRECT OR CONSEQUENTIAL, ARISING OUT OF THEIR USE.