

Tyvek.

DUPONT™ TYVEK® STRAIGHTFLASH™



How it works: DuPont™ StraightFlash™ is designed to protect the heads & jambs of rectangular windows and doors from water intrusion.

A flashing material for straight jambs and heads of windows and doors.

DuPont[™] StraightFlash[™] is a premium self- adhered flashing material that is ideal for helping to protect heads and jambs of windows and doors. By bridging the interface between the fenestration and the water-resistive barrier, DuPont[™] StraightFlash[™] protects these vulnerable areas that are so often subject to potential water damage.

When used as part of the DuPont Weatherization System, DuPont™ StraightFlash™ also helps contribute towards U.S. Green Building Council LEED® points, LEED® for Homes points, and The National Green Building Standard™, as well as helping to create more sustainable, durable structures.

BENEFITS

Superior protection from water damage

- 100% butyl sealant provides excellent adhesion to most common building materials
- Meets the AAMA 711-13 material standard at the highest classification levels: Class A (no primer) and Level 3 Thermal Exposure (80°C / 176°F for 7 days)
- Meets and Exceeds ASTM E331 Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference: no leakage at 300 Pa (equivalent to 50 mph windload), even after thermal aging (0-120°F)
- Does not contain asphaltic / bitumen adhesive materials
 which many window manufacturers prohibit due to
 adverse material reactions, such as black staining, oozing,
 and deformation over time, particularly with vinyl flanges.
- Can be installed at external temperatures as low as -4°C (25°F) as long as the surface is clean and free from frost and ice

Easy installation

- Forgiving initial tack provides ability to correct installation mistakes
- Features quick-release, scored backing
- Packaged in ready-to-use 4" x 150 ft or 9" x 125 ft rolls in an easy dispensing carton

Superior durability

- Constructed with a durable, micro-creped DuPont[™]
 Tyvek® top-sheet, a 100% butyl adhesive layer, and a specially designed, scored release liner
- Designed to withstand up to 270 days of UV exposure
- Tough, tear-resistant

Excellent adhesion performance

- 100% butyl adhesive performs through extreme temperatures
- Adheres to most common building materials



DUPONT™ STRAIGHTFLASH™

THE DUPONT™ BUILDING KNOWLEDGE CENTER

All DuPont building envelope systems products are backed by industry-leading building science and unrivaled industry support provided by The DuPont™ Building Knowledge Center, your source for the DuPont product information and technical support you need to build quality, durable and energy-efficient structures.

DUPONT™ TYVEK® SPECIALIST NETWORK

A national group of highly trained field representatives is available to assist you with your installations. From the latest updates on building codes, to keeping up with current trends and challenges, your local DuPont™ Tyvek® Specialist can provide on-site consulting and training to help you make sure the job gets done right.



DUPONT™ TYVEK® CERTIFIED INSTALLERS

The DuPont[™] Tyvek[®] Certified Installer Network is one more way to put the building science expertise of DuPont right at your fingertips. Your DuPont[™] Tyvek[®] Certified Installer provides trained installation services for DuPont Weatherization Products to help seal the building envelope. To locate a certified installer in your area, please visit www.weatherization.tyvek.com.

LIMITED WARRANTY

DuPont[™] StraightFlash[™] is backed by a limited warranty. For more information please visit www.weatherization.tyvek.com or call 1-800-44-Tyvek.

For more information please visit www.weatherization.tyvek.com or call 1-800-44-Tyvek

COMPLETE SYSTEM OF PRODUCTS

For optimal protection on all your building projects, use DuPont™ StraightFlash™ with the complete line of DuPont building envelope systems products, including:

Building Wraps:

DuPont[™] Tyvek[®] HomeWrap[®]
DuPont[™] Tyvek[®] StuccoWrap[®]
DuPont[™] Tyvek[®] DrainWrap[™]
DuPont[™] Tyvek[®] ThermaWrap[®] R5.0
DuPont[™] Tyvek[®] ThermaWrap[®] LE

Flashing Systems:

DuPont[™] FlexWrap[™] NF DuPont[™] StraightFlash[™] DuPont[™] StraightFlash[™] VF DuPont[™] Flashing Tape

Accessories:

DuPont™ Tyvek® Tape
DuPont™ Residential Sealant
DuPont™ Tyvek® Wrap Caps
DuPont™ Adhesive/Primer
DuPont™ Window & Door Foam
DuPont™ RainVent™ Battens

Roofing Underlayments:

DuPont[™] Tyvek[®] Protec[™] 120 DuPont[™] Tyvek[®] Protec[™] 160 DuPont[™] Tyvek[®] Protec[™] 200



DuPont[™] StraightFlash[™] helps contribute towards earning U.S. Green Building Council LEED[®] points and other green building certification program points.

